Smart PSS V2.02.1


Dahua Technology

SmartPSS

Smart Professional Surveillance System


An easy-to-use security surveillance application with friendly interface.


Designed for small or medium daily-use system. Provide efficient device management, monitoring, playback, alarm, video analytics, video wall, etc.



What's new? -26 language







Alarm sound and event account CPU & RAM

- Drag to change the arrangement
- Open a new fuction page
- Check the CPU & RAM
- Show the time which is same to the PC
- New system config change to the top-right corner

64

system config

14:50:53

Initialization of the password

Initializat	ion	*		Initialization		
1.Password Setting	2.Password Protection		1.Passwo	rd Setting	2.Password F	rotection
			O Please se	et security questions!		
Please set admin passwor	d at first installation l		Question 1	What is your favorite childre	en's book?	
Password			Answer			
Password Strength			Question 2	What was the first name of	your first boss?	
Confirm Password			Answer			
Auto Login after Registration			Question 3	What is the name of your f	avorite fruit?	
			Answer			
	Next Canc					Finish

- There is no normal password of the admin, U should set the password first
- When U forget your password, U can use the security questions to reset the password

Installation

Windows administrator

non-Windows administrator

New > Installation by Windows administrator, operation by non-Windows administrator

Old > Installation by Windows administrator, operation also by Windows administrator

Initialization of the password




• U can initialize the password by the security question

	Password Reset	×
🕛 Plea	se reset admin password!	
Passwore	d la	
Password	d Strength	
Confirm F	Password	
	0	×
TV		1
	Password Reset	
O Please and	swer these security questions!	
Question 1	What is your favorite children's book?	
Answer		
Question 2	What was the first name of your first boss?	
Answer		
Question 3	What is the name of your favorite fruit?	
Answer		
	Next Can	cel

now

System Config

	System Config X	
Base	Base	в
	Initial page: Resume last page 👻	
Live View	Maximum behaviour: Full screen Maximum window	Live
Playback	Minimum behaviour: 🦉 Show floating window	Pla
	Default video scale: 🔍 Original 🌑 Expanding	
Device	Default device tree: Region Tree(By Channel) -	De
	Active after restart. Used for liveview, playback, and video wall.	
Event	Live View	E
Log	Instantly replay time: 5minutes +	Ĺ
	🖉 Resume last preview	
ystem & Language	Playback	System 8
Hot Keys	Save device tree selection	Hot
	Device	
File Path	Show device channel number	File
Device Devices	3 Auto login device	
Backup/Restore	Auto fill user and key	Backup
	Device login user: 👘 admin	4
	Device login key: •••••	
	Apply Save Cancel	
	MAR MARCH	
	Apply Save Cancel	



Device management

		🔆 Impoi	n ye	xport				All Devices: 4	Online Devices: 4
All Device	ncode Device								
🗆 No. 🛛 Nam	e 🔺 IP/Domain Name	Туре	Model	Port	Channel Number	On	line Status	SN	Operation
1 1-0-0	10.15.6.82	NVS	ARC6416	40008	4/0/16/4	0	Online	1L0150DYAQ00003	0 @ [> 10
2 10.15.6	.19 10.15.6.19	IPC	IPC-HF8	37777	1/0/2/2	•	Online	00:12:34:56:79:9a	0 🌣 🕞 🗓
3 10.15.6	.85 10.15.6.85	NVR	DH-NVR	40009	8/0/4/2	0	Online	2E03EBCPAZA40D3	\$\$\$\$ [⇒ 10
4 PCNV	R 10.18.116.171	PC-NVR	PC-NVR	37777	32/0/0/0	۲	Online	N/A	0 🔅 🗗
						ļ	Auto Searci		
					Device Segr	ment:	10 . 18	.116 . 0 - 10 . 18 .11	6 .255 Search
		⊖ Refre	sh 🕑 M	lodify IP				Sear	ch Device Number:
		🗆 No.		IP		Туре		Mac	Port
							Mod	lify the device IP	
					New IF	5			Ĩ
					SubM	ask			
					Gatew	av			
	(13			0.000	- ,			


- Auto find & add devices in specific network segment range of 255.
- Add device manually by:
 - IP address
 - DDNS domain
 - P2P
- Import & Export devices to share devices on multiple clients
- Check & Export status of online devices, connection, etc.
- Modify IP of the devices searched, Batch or Manual

Custom Layout



- Custom layouts to fit various monitor scenes
- Adjust videos with different aspect ratios: 4:3, 16:9, full-screen, etc.
- Save custom views for tour & reuse.

WATCH VIDEO



PTZ Control



- PTZ camera control
 - Control PTZ with arrow button
 - Zoom in/out
 - Control PTZ with mouse on the
 - preview window
 - Set preset, Tour, etc.

Smart Track Link a fish eye and speed dome



Calibration

- Link a fish eye and speed dome(s)
 - Overview image of fish eye camera
 - Reginal details from speed dome
 - Point and track by manual

Operation


- Precise and fast
- Simple calibration

Smart Track Link a bullet and speed dome




- Link a bullet and speed dome
 - Overview image of bullet camera
 - Reginal details from speed dome
 - Point and track by manual
 - IVS track automaticly
 - Precise and fast
 - Simple calibration

Calibration




Playback



- New device video file list which support
- filtering video types
- Add local video and image file, the file display support thumbnail and list
- Picture play supports automatically play next, also supports full-screen play
- Support reverse play, single frame backward
- Add the intelligent recording type in search recording type



Smart Search



 When you spot an area of interest, click to jump to playback of the corresponding motion detection video fragment.




WATCH VIDEO





- Support face capture of ultra-smart IPC.
- You can check face snapshot in LOG interface.

Sish Eye Dewarping




- Support fisheye dewarp of fisheye camera in preview and playback.
- Support three installation modes: ceiling mounted, wall mounted and ground mounted for fisheye Camera.
- Support 8 kinds of dewarping view.

WATCH VIDEO




IVS – Intelligent Video Analytics



- Interactive configuration of IVS tools :Tripwire, Intrusion, Abandon Detection and Scene Change
- Display real-time IVS event detection



Map – Link Geo Info




- Levels Maps One large map and multiple small areas.
- Set cameras and their locations on map.
- When a channel has an alarm attached to it, the icon of camera will turn red.

🔡 Video Wall




- Editing of layouts for an additional monitor is performed on the main computer monitor.
- New layout is instantly switched when saved.
- Brand new Video Wall, compatible matrix, decoder, splicing controller
- A variety of open window method
- Playback on the video wall if the device supports
- The window tour, plan tour
- Support NKB1000 control

People Counting



- Retrieve people counting data from supported cameras.
- Support search counting data in various criteria.
- Data can be displayed in Line Chart view or Bar Chart.
- Each direction statistics can be viewed separately.


Heat Map



- Show the high or low popularity area
- Support backup & search

	PC-NVR Setting	Password	d:	
	Password Setting		OK Cance	
自定义	Quit	Checkt	the password now if we	
			quit the PC-NVR	
			A	
		Deseurad Catting	TA T	A
etting		Password Setting		
		Vser:	admin	
IP. 10.18.116	3: 171	Original Password	1:	
Port: 37777		New Password:		
Version: V3.0		Level:		
AutoRun:		Confirm:		

PC - NVR



- Choose recording stream type
- Main stream or sub stream
- Set recording plan
- ✓ Regular
- ✓ Motion detect
- ✓ Alarm
- ✓ Motion detect & Alarm
- ✓ Smart
- Set pre-recorded/delayed time

Access

	Console		SMART PSS	Access +			• • • • •	— × 10:11:11
i	User			a [·			
A	Access Control 🔹		▼ 👫 Default Group	Door 1	Door 2			
	Timezone Holiday Access Level User Right First Card Unlock Multi-card Unlock Anti-passback		 10.15.5.187 10.15.5.81 10.15.5.81 10.15.5.88 10.15.6.144 10.15.6.221 10.15.6.250 10.15.6.250 10.15.6.84 10.15.6.84 10.15.6.86 10.15.6.96 					
	Inter-door Lock		🗠 10.18.116.14 🖓 10.18.116.34	EISL D	View			
	Remote Verification		🚜 10.18.116.42 🐼 10.18.116.74		🗹 All 🛛 🗹 Alarm	🗹 Abnormal 🗹 Normal		₫ ७
2	Event	A	🚜 192.168.1.10 🧟 10.15.23.211	1 Time	Event Descri	ption Operation	ID: Name:	
Ŵ	Log		Q 10 15.5.38 Q 10 15 6 67 Global Control				Department: Tel:	
(O	Attendance •		Always O Always	<u>с</u>			Card No.:	
		1	Giobal Control Always O Always	a		11	Card No.	14

Console

User management Permission function

- Door group right
- User right
- First card unlock
- Multi-card unlock
- Anti-pass back
- Inter-door lock
- Remote verification
- Period setup
- Holiday setup
- Event CFG

Log

VDP – Video Intercom




- Allow users to talk with VTO & VTH and receive call from them.
- Make it easy to manage all the video intercoms and CCTV products simultaneously.
 - Publish messages to VTH.

•

- Information inquiry, such as alarm record, unlocking record, call record.
- Support card issuing.

VDP – Video Intercom



- Live view
- Talk
- Message Publish
- Information Inquiry
 - Alarm record
 - Unlocking record
 - Call record
- Card Issuing
- VTS Center

Attendance Console

User management Attendance Setting

- Door group right
- Attendance time zone
- Attendance shift
- Holiday


Shift schedule

Report

SMART PSS	Device	s Attendand	ce +				0) ± ☆
Organizatio	Attenda	nce Device Name	Card No.	ID	Name	Department	Time
Search	Q	ASA	8 4	32	jack	Department1	2017-11-30 09:45:30
	~	ASA			B1E43B12	Department1	2017-11-30 09:44:34
9							
						Details	
			-		-		Time: 2017-11-30 09:45:3
							Card No.: 8 4
							ID: 32
			har				Name: jack
		1/1	View				Department: Department1
					jack 32		
-		Per			Department1		
Access point as Attendar	nce:	-					
		Million			Department1		

Attendance Rule

Shift schedule



- Attendance rule setup include attendance device, period, shift and holiday.
- Shift schedule support user shift, temporary shift and new user auto shift
- Support attendance data manual extraction
- Support ASI1212D access control device input


Attendance Report :

- ✓ Statistics
- ✓ Detail
- ✓ Overtime
- ✓ Exception
- ✓ Break out
- ✓ Leave

SN	IART PSS	De	vices Atte	ndance +					• * ~
Ì	Time: 2017	/11/30-2017/11/30	E Pe	rsonnel/Name:		Department:	All	•	Search Bac
2						Exception:	All	Ť	
	Statistics	Detail	OverTime	Exception E	Break Out	Leave			Ex
	Date	Name	User ID	Department	Sign In		Sign Out	Туре	Operation
		B1E43B12	30	Department1	09:44	N	ot Sign out	Absent	Ø
8	2017-11-30	01040012		and the second second					

No./Page 20 🔻

o./Page 20 🔻



Sma	rtPSS	
SIIIG	100	

Specification

	Supported Devices	DVR, NVR, IPC, NVS, Video Wall Controller, NKB, VDP, ASC				
	Max. Management Devices	64				
Devices & Users Video	Max. Management Channels	256				
	Max. number of Users	50				
	Compression Format	H.265/H.264/MPEG-4/JPEG/SVAC				
NUK	Display Resolution	up to 4000 x 3000				
Live Preview	Video Display Split	1/4/6/8/9/16/25/36 or customized split for Mac, up to 64 for Windows				
	Max. Preview Screen	4				
	Features	Snapshot, E-PTZ, Audio, Record, Talk, Instant playback, Tour task, View, Fisheye imag correction, IVS, Stream control, Optional video scale, Smart track config				
Ma	Max. Channels	36				
	Max. Task of Export	10 once				
Playback	Features	Snapshot, E-PTZ, Audio, Speed 1/8x~8x, Synchronization playback, Fisheye image correction, IVS, Faster/Slower play, Optional video scale				
Recoding	PC-NVR	32 Channels				

SmartPSS Specification of intelligent building

Devices	Supported Devices	VTO, VTS, ASC, ASM
	Max. Management ASC	64
ASC	Max. number of Users	10K
XM	Max. number of Event log	100K
	Max. Management VTO	64
VDD	Max. Management VTH	256
VDP	Max. Management VTS	8
	Max. number of VDP Users	10K
Attendance	Max. number of Attendance Devices	10



Zhejiang Dahua Technology CO., LTD

Overseas Business Center